

The Kenya Power & Lighting Co. Ltd.

TITLE:

SPECIFICATION FOR
CABLE GRIP (COME
ALONG CLAMP) FOR
BARE ACSR ,AAAC &
COPPER
CONDUCTORS-For use
by Transmission Line

Teams

Doc. No.	KPLC1/3CB/TSP/09/008
Issue No.	1
Revision No.	0
Date of Issue	2011-01-17
Page 1 of 1	0

TABLE OF CONTENTS

- 0.1 Circulation List
- 0.2 Amendment Record

FOREWORD

- 1. SCOPE
- 2. REFERENCES
- 3. TERMS AND DEFINITIONS
- 4. REQUIREMENTS
- 5. TESTS AND INSPECTION
- 6. MARKING, PACKING AND INSTRUCTIONS

ANNEX A: Guaranteed Technical Particulars (to be filled and signed by the manufacturer and submitted together with copies of the manufacturer's catalogues, brochures, technical data, customer sales records & reference

letters and test reports for tender evaluation)

ANNEX B: TYPICAL DESIGN OF CABLE GRIP (COME ALONG CLAMP)

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed: Ter	Signed: (b. alluge
Date: 2011-01-17	Date: 2011-01-17



_	_	-		
1		П	Т	⋤.
			_	.

10000 1101	1
Revision	
No.	0
Date of Issue	2011-01-17

0.1 Circulation List

COPY NO.	COPY HOLDER	
1	Research & Development Manager	
2	Procurement Manager	
3	Stores & Stock Control Manager	
4	Transmission Manager	
5	Deputy Manager, Technical Audit	

0.2 Amendment Record

Rev No.	Date	Description of Change	Prepared by	Approved by
Ĭ	(YYYY-MM- DD)		(Name & Signature)	(Name & Signature)
				,

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed: Electe	Signed: (be actinge
Date: 2011-01-17	Date: 2011-01-17



SPECIFICATION FOR
CABLE GRIP (COME
ALONG CLAMP) FOR
BARE ACSR, AAAC &
COPPER
CONDUCTORS-For use
by Transmission Line

Teams

TITLE:

Doc. No.	KPLC1/3CB/TSP/09/008
issue No.	1
Revision No.	0
Date of Issue	2011-01-17
Page 3 of	10

FOREWORD

This specification has been prepared by the Research and Development Department in collaboration with Transmission Department both of The Kenya Power and Lighting Company Limited (KPLC) and it lays down requirements for cable Grip (come along Clamp) for Bare AAC, ACSR, AAAC & Copper Conductors. It is intended for use by KPLC in purchasing the Cable Grips.

The supplier shall submit information which confirms satisfactory service experience with products which fall within the scope of this specification.

1. SCOPE

- 1.1 This specification is for portable hand held grooved clamps for gripping bare ACSR and copper conductors of the following diameter ranges
 - 1.1.1 3-15mm
 - 1.1.2 7.5-20mm
 - 1.1.3 15-35mm
- 1.2 The equipment shall be used for gripping while tensioning bare & insulated AAC conductors, ACSR , AAAC and copper conductors
- 1.3 The grip has to be firm and non-slip and should not cause any damage to material being pulled.

2. REFERENCES

The following standards contain provisions which, through reference in this text constitute provisions of this specification. Unless otherwise stated, the latest editions (including amendments) apply.

ISO 2766- Single Lifting Hooks with Shanks-capacity up to 25tonnes-Grades M,P,S, (T,V)- Hummer & Dropped Forged Hooks.

BS EN 3243-Specification for Hand- Operated Chain Blocks.

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed: Hen te.	Signed: (in cittige
Date: 2011-01-17	Date: 2011-01-17



TI	T	LE:

Teams

Doc. No.	KPLC1/3CB/TSP/09/008
Issue No.	1
Revision No.	0
Date of Issue	2011-01-17
Page 4 of	10

BS EN 1677-5 - Components for Slings.Safety. Forged Steel lifting Hooks with Latch.

3. TERMS AND DEFINITIONS

N/A

4. REQUIREMENTS

4.1 Construction

- 4.1.1 The clamp shall be special spring loaded to prevent the grip from falling off the conductor and should allow instant release without jamming when the tension is removed.
- 4.1.2 The jaws of the grip shall be V grooved for maximum contact area without damage and shall have mechanism for holding it open for easy placement of conductor.
- 4.1.3 The construction material shall be drop forged quality steel, machined and heat treated. The equipment shall be weather proof.

4.2 Operation.

- 4.2.1 The grip shall when opened remain in open position for easy placement on conductor
- 4.2.2The grip shall close as tension is applied and hold conductor firmly.
- 4.2.3The spring load shall allow for easy removal upon removal of tension without jamming.

4.4 TECHNICAL AND SPECIFIC REQUIREMENTS

4.4.1 Specific requirements:

4.4.1.1 The same jaws shall be able to grip steel guy wires and extra high strength conductors within its diameter range.

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed: Let fei	Signed: (1 other
Date: 2011-01-17	Date: 2011-01-17



The Kenya Power & Lighting Co. Ltd.

TITLE:

SPECIFICATION FOR
CABLE GRIP (COME
ALONG CLAMP) FOR
BARE ACSR ,AAAC &
COPPER
CONDUCTORS-For use

by Transmission Line Teams

Doc. No.	KPLC1/3CB/TSP/09/008
Issue No.	1
Revision No.	0
Date of Issue	2011-01-17
Page 5 of 1	0

4.4.1.2 The pulling force and maximum grip diameter shall be specified.

4.4.2 Technical Specifications. a) 3-15mm

ltem No.	Technical Description	KPLC Technical Requirements
1	Material of clamp	Drop forged heat treated steel
2	Clamp jaws	Double Round
3	Safe working load	2000 kgs
4	Breaking load	12000 kgs
5	Maximum tensile strength	1770N/mm2
6	Grip range	3-15mm
7	Weight	< 7kgs
8	Finishing	Corrosion resistance coating
9	Warranty on Equipment	At least 12 months
10	International standards	IEC ,ISO & BS Stardards
11	Test certificate/ Test Report	Required
12	Operation and maintenance manual	Shall be in English language

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed:fei	Signed: (10 cettlings
Date: 2011-01-17	Date: 2011-01-17



Teams

Doc. No.	KPLC1/3CB/TSP/09/008
Issue No.	1
Revision No.	0
Date of Issue	2011-01-17
Page 6 of 1	0

b) ACSR, AAC, Copper 7.5- 20mm

Item No.	Technical description	KPLC Technical Requirements
1	Material of clamp	Drop forged heat treated steel
2	Clamp jaws	Double Round
3	Safe working load	2000 kgs
4	Breaking load	12000kg
5	Maximum tensile strength	1960N/mm2
6	Grip range	7.5-20mm
7	Weight	< 10 kgs
8	Finishing	Corrosion resistance coating
9	Warranty on Equipment	At least 12 months
10	International standards	IEC ,ISO & BS Stardards
11	Test certificate/ Test Reports	Required
12	Operation and maintenance manual	Shall be in English language

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed: The ter	Signed: We attack
Date: 2011-01-17	Date: 2011-01-17



SPECIFICATION FOR
CABLE GRIP (COME
ALONG CLAMP) FOR
BARE ACSR ,AAAC &

COPPER
CONDUCTORS-For use
by Transmission Line
Teams

Doc. No.	KPLC1/3CB/TSP/09/008
Issue No.	1
Revision No.	0
Date of Issue	2011-01-17

c) ACSR, AAC, Copper 15-35mm

TITLE:

Item No.	Technical description	KPLC Technical Requirements
1	Material of clamp	Drop forged heat treated steel
2	Clamp jaws	Double Round
3	Safe working load	2000 kgs
4	Breaking load	12000 kg
5	Maximum tensile strength	1960N/mm2
6	Grip range	15-35mm
7	Weight	< 15kgs
8	Finishing	Corrosion resistance coating
9	Warranty on Equipment	At least 12 months
10	International standards	IEC ,ISO & BS Stardards
11	Test certificate/ Test Report	Required
12	Operation manual	Shall be in English Ianguage

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed: Hen tei	Signed: (haltye
Date: 2011-01-17	Date: 2011-01-17



Ţ	ľ	Γ	L	Ε	•

Teams

Doc. No.	KPLC1/3CB/TSP/09/008
Issue No.	1
Revision No.	0
Date of Issue	2011-01-17
Page 8 of 1	0

5.0 TEST AND INSPECTION

- 5.1. The clamp shall be inspected and tested in accordance with the requirements of this specification and relevant IEC/ISO /BS Standards.
- 5.2 Copies of previous test reports for the cable grips shall be submitted with the tender for evaluation. The test reports must be from an ISO/IEC 17025 accredited laborotary.
- 5.3 Test report for the clamps manufactured for KPLC shall be submitted to KPLC for approval before shipment/delivery. The test reports shall include tensile strength and breaking load of the clamp.

6 MARKING, PACKING AND INSTRUCTIONS

- 6.1 The following information shall be marked indelibly and legibly on the cable grip (come along clamps)
 - Manufacturer's Name or Trademark;
 - ii) Type reference
 - iii) Safe working load
 - iv) Serial number
 - v) Production batch and year of manufacture
 - vi) Letters "KPLC"
- 6.2 Instructions for use shall be submitted with the clamps during delivery (all in English Language).
- 6.3 The clamps shall be packed in wooden crates and shall be protected from damage during transportation and storage.

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D		
Signed: The fei	Signed: Coulting		
Date: 2011-01-17	Date: 2011-01-17		



Т	1	7	1	F	Ξ	•
- 1	1	1		٠,	_	1

Teams

Issue No.	1
Revision No.	0
Date of Issue	2011-01-17

ANNEX A: Guaranteed Technical Particulars (to be filled and signed by the <u>Supplier</u> and submitted together with copies of manufacturer's catalogues, brochures, drawings, technical data, sales records and copies of certificates/test reports for tender evaluation)

Clause number	Bidder's offer (indicate full details of the offered equipment for each requirement of the specification and indicate supporting document submitted).
1. Scope	
1.1-1.3	
4. Requirements	
4.1Constuction	
4.1.1- 4.1.3	
4.2 Operations	
4.2.1-4.2.3	
4.4 Specific Requirements	
4.1.1.1-4.4.1.2	
Technical Specifications	
a) 3-15mm	
Requirements 1-12	
b) 7.5-20mm	
Requirements 1-12	
c) 15-35mm	
Requirements 1-12	
5.0 Tests and Inspection	
5.1-5.3	
6.0 Marking & Instructions	
6.1-6.3	

Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed: Fer.	Signed: (lo-cuttige
Date: 2011-01-17	Date: 2011-01-17

Supplier's Name, Signature, Stamp and Date



Т	ľ	T	L	E	•

Teams

Doc. No.	KPLC1/3CB/TSP/09/008
Issue No.	1
Revision No.	0
Date of Issue	2011-01-17
Page 10 of	10

ANNEX B: TYPICAL IMAGE OF CABLE GRIP (COME ALONG CLAMP)



Issued by: Head of Section, Tech Stds & Specs	Authorized by: Head of Department, R&D
Signed:fei	Signed: (be outline
Date: 2011-01-17	Date: 2011-01-17