	DESCRIPTION	
ITEM		MANUFACTURE'S
A	DESK- 30mm thick	COMMENT
i.	L-shaped Desk (1800mm x 1400 x 720) mm	
	L-Type desk overall Size 1,800 x 1000 x 720mm (w x d x h	
	in scratch proof laminated MDF. To have:	
	Powder coated steel legs and with steel modesty	
	panel. To have:	
	> Fully integrated wire management function with	I I
	operable horizontal and vertical ducts, gromme	
	holes with caps on and Tee – nut locking mechanism	
	Punched openings finished with molded plastic grey	
	caps on the outer corners of the desk giving users two	
	cable access options.	
	Surface should be finished with a soft grain hea	
	resistant, water proof and smooth durable laminate	;
	that is friendly to the skin and easy to clean.	
	> 3 tire pedestal that flashes with the of the desk.3-ties	1
	drawer pedestal 400 x 530 x 720mm (w x d x h)	
	flashing the desk to make the entire workstation size	
	to be 1800 x 1400 x720mm (w x d x h), should have	
	a pencil drawer at the top, a regular drawer in the	
	middle and a deep file drawer complete with hanging	
	rails at the bottom and supplementary wheel to	
	prevent the pedestal from falling when open.	
-	The edge of the overall top panel to be finished in	
	PUR molded edge/injected urethane which should be	
	soft yet sturdy to ensure safety and durability	
	> To be beech wood in color.	

Kindly sign and stamp as indicated below:
Signature of duly authorised person for and on behalf of the Manufacturer.
Name and Capacity of duly authorised person signing on behalf of the Manufacturer

ii.		ped Desk (1400mm x 1400 x 720) mm	
		e desk overall Size 1400 x 1000 x720mm (w x d x h) in	
	scratch	proof laminated MDF. To have:	
	>	Powder coated steel legs and with steel modesty	
		panel. To have:	
	4	Fully integrated wire management function with	
		operable horizontal and vertical ducts, grommet	
		holes with caps on and Tee – nut locking mechanism.	
	>	Punched openings finished with molded plastic grey	
		caps on the outer corners of the desk giving users two	
		cable access options.	
	>	Surface should be finished with a soft grain heat	
		resistant, water proof and smooth durable laminate	
		that is friendly to the skin and easy to clean.	
	>	3 tier pedestal that flashes with the of the desk.3-tier	
		drawer pedestal 400 x 530 x 720mm (w x d x h)	
		flashing the desk to make the entire workstation size	
		to be 1400 x 1400 x720mm (w x d x h), should have	
		a pencil drawer at the top, a regular drawer in the	
		middle and a deep file drawer complete with hanging	
		rails at the bottom and supplementary wheel to	
		prevent the pedestal from falling when open.	
	>		
		PUR molded edge/injected urethane which should be	
		soft yet sturdy to ensure safety and durability	
	>	To be beech wood in color.	
iii.	Round	table – 1200mm diameter	
	>	1200mm diameter round table to stand on metal legs.	
		The table surfaces should be finished in scratch proof	
		laminated MDF, a soft grain heat resistant, water	
		proof and smooth durable laminate that is friendly to	
		the skin and easy to clean.	
	>	To be beech wood in color.	

Kindly sign and stamp as indicated below:		
Signature of duly authorised person for and on behalf of the Manufacturer.		
Name and Capacity of duly authorised person signing on behalf of the Manufacture		

IV.	Secretarial desk	
	L-type desk with counter top	
	Overall size 1,600 x 1,500 x 1,050mm in scratch proof laminated MDF.	ı
	Counter top of 2 tier overall size 1,600 x 450 x	
	600mm	
	Powder coated steel legs and with steel modesty panel	
	Fully integrated wire management function with operable horizontal and vertical ducts, grommet hole with caps on.	
	Punched openings finished with molded plastic gre- caps on the outer corners of the desk giving users two cable access options.	l .
	Surface should be finished with a soft grain hear resistant, water proof and smooth durable laminate that is friendly to the skin and easy to clean.	
	To have a side cabinet with 2 tier shelving and with a solid door on one end and a 3D fixed drawer with a pencil drawer at the top, a regular drawer in the middle and a deep filer complete with rails at the bottom.	
	 The desk to have adjustable grommet holes with caps 	
	The desk to have adjustable grofffliffer holes with capsTo be beech in color.	
	A wear would to the	
v.	4 - way workstation	
	A cubical system workstation in Kenya Power corporate blue panel. Overall size 2,980 x2,800 mm and Comprising of;	
	Beech wood colored,4No. L-shaped worktops in	
	scratch proof laminated board on both	
	side1,400x1,400x750mm (w x d x h) (inclusive of a	
	pedestal that flushes with the desk)	
	 Fully integrated wire management function with 	
	operable horizontal and vertical ducts, gromme	
	holes with caps on and Tee – nut locking mechanism	
Ki	ndly sign and stamp as indicated below:	

Signature of duly authorised person for and on behalf of the Manufacturer.

Name and Capacity of duly authorised person signing on behalf of the Manufacturer

	>	3D pedestal (2 drawers + 1 filing) overall size	
		401x450x725mm, with matt nickel plated handles for	
		each station	
	>	Metal leg table base equipped with 20 - 25mm height	
		adjustable plastic foot for leveling unevenness of the	
		floor.	_
	>	60mm thick aluminum extruded frame partition with	
		glass divider adapted for visibility and edges to be	
		finished with urethane or pur-form edges to reduce	
		abrasion	
	>	The workstation to consist of 8No. aluminum	,
		extruded frame partition and 3No. joints to allow the	
		L-shaped worktops face similar direction.	
vi.	2- way	workstation	
		cal system workstation in Kenya Power corporate blue	
		Overall size 1520 x 2,800mm and Comprising of;	
	>	Beech wood colored, 2 No. L-shaped worktops in	
		scratch proof laminated board on both	
		side1,400x1400x750mm (w x d x h) (inclusive of a	
		pedestal that flushes with the desk)	
		Fully integrated wire management function with	
		operable horizontal and vertical ducts, grommet holes	
		with caps on and Tee – nut locking mechanism.	
	>	3D pedestal (2 drawers + 1 filing) overall size 401 x	
		450 x 725mm, with matt nickel plated handles for	
-		each station	
	A	Metal leg table base equipped with 20 - 25mm height	
		adjustable plastic foot for leveling unevenness of the	
		floor.	
	>	60mm thick aluminum extruded frame partition with	
		glass divider adapted for visibility and edges to be	
		finished with urethane or pur-form edges to reduce	
		abrasion	

Kindly sign and stamp as indicated below:		
Signature of duly authorised person for and on behalf of the Manufacturer.		
Name and Capacity of duly authorised person signing on behalf of the Manufacture		

		7 10
	The workstation to consist of 5No. aluminum	
	extruded frame partition and 2No. joints to allow the	
	L-shaped worktops face similar direction.	
vii.	Conference- table 50mm thick 50mm thick conference table: High quality well-polished dyed mahogany and scratch resistant both on top & desk panel Overall size 3,000 x 1,200 x 750mm with panel legs and demountable components. Allow for integrated horizontal and vertical cable management system complete with power, LAN and telephone points.	
В	<u>CHAIRS</u>	
i.	 Medium back leather chair ➢ Medium back genuine leather upholstered ➢ Black in color ➢ Chair size 680 x 690 x 1150/1250mm (w x d x h) ➢ Arms to be made of top grade plastic armrest ➢ To be on multi synchronized tilt mechanism ➢ Support upper and lower- ergonomically design, structured to provide spine comfort. ➢ The base to be 5-star polished aluminum die-cast and on urethane dual wheel castors. 	
ii.	 Medium back cantilever leather chair Medium back cantilever chair in genuine leather finish ➤ Chair size 629 x 710 x 944mm (w x d x h) ➤ Black in color ➤ Top grade plastic armrest and base, assembled without bolts complete with chrome polished base. ➤ To match the medium back leather chair above 	

Kindly sign and stamp as indicated below:
Signature of duly authorised person for and on behalf of the Manufacturer.
Name and Capacity of duly authorised person signing on behalf of the Manufacturer

0.00	
iii.	High back fabric chair
	High back chair with lumbar support, gas lift mechanism,
	heavy duty fabric finish seat and back
	Seat and headrest to be grey in color and the back to
	be Kenya Power blue.
	➤ Chair size 590 x 640 x 1180mm (w x d x h).
	The base to be 5-star polished aluminum die-cast and
	on urethane dual wheel castors.
	tilt locking handle, synchronized tilt.
1	> Tile tension adjustment: side of the seat Gas sprays;
	height adjustment 100-125mm. Release ball casters.
	> Arms to be made of top grade plastic armrest
	Finished in high quality water repellant, burn proof
	fabric.
	The back to have 5 tilting lock positions and lumbar
i	support pad that adjusts automatically depending on
	the tilting angle.
iv.	Medium back fabric chair
	Medium back chair with lumbar support, gas lift mechanism,
	fabric finish seat and back.
	> Seat and headrest to be grey in color and the back to
	be Kenya Power blue.
	Chair size 610 x 660 x 980/1,050mm (w x d x h).
	➤ The base to be 5-star polished aluminum die-cast and
	on urethane dual wheel castors.
	> Arms to be made of top grade plastic armrest
	> Tile tension adjustment: side of the seat Gas sprays;
	height adjustment 100-125mm. Release ball casters.
	Finished in high quality water repellant, burn proof
	fabric.
	To match high back fabric chair above.
v.	Medium back cantilever fabric chair
	Medium back cantilever chair in fabric finish
	Seat and headrest to be grey in colour and the back
	to be Kenya Power blue
	➤ Chair size 629 x 710 x 944mm (w x d x h)

Kindly sign and stamp as indicated below:

Signature of duly authorised person for and on behalf of the Manufactures

Name and Capacity of duly authorised person signing on behalf of the Manufacturer

	IXI 1/7A:174 O 1/002/1	7 10
	> Assembled without bolts complete with chrome	
	plated base	
	Arms to be made of top grade plastic armrest	
	Finished in high quality water repellant, burn proof	
	fabric fabric	
•	To match the high back fabric chair	
vi.	2-link chair	
	2 - linked visitor's bench in perforated steel sheet seat pan,	
	surface mount finish in polyester powder coat. The perforated	
	steel to be gauge 16 on both the back rest and the seat board.	
	Components of the chair to be assembled using Allen key bolts, screws/fasteners	
vii.	3-linked chair	
V 11.	3 - linked visitor's bench in perforated steel sheet seat pan,	
	surface mount finish in polyester powder coat. The perforated	
	steel to be gauge 16 on both the back rest and the seat board.	
	and the search of the search o	
viii.	Cashier/ Draughtsman chair	
	High quality cashier/Draughtsman medium back	
	nonflammable fabric chair with arms, gas lift mechanism.	
	Aluminum die casting 5-star base easily adjustable	
	Chrome coated footrest and dual ball castors.	
C	FILING	
i.	4 tier half glass filing cabinet	
	4 tier filing cabinet 900 x 495 x 1,500mm (w x d x h). Features;	
	Scratch proof laminated MDF.	
	Double glass doors for the upper 2 shelves and	
	double wooden doors for the lower 2 shelves	
	> Surface should be finished with a soft grain heat	
	resistant, water proof and smooth durable laminate	
	that is friendly to the skin and easy to clean	
	The base to have adjustable plastic tabs for leveling	
	unevenness of the floor.	
	Color – beech wood	

Signature of duly authorised person for and o	on behalf of the Manufacturer.
Name and Capacity of duly authorised person	n signing on behalf of the Manufacture

Kindly sign and stamp as indicated below:

ii.	2 tier 2 door cabinet	
	2 tier 2 door cabinet 1200 x 400 x 930 (w x d x h). Features;	
	To be made in scratch proof laminated MDF	
	Double wooden lockable door fitted with matt	
	nickel plated handles	
	Surface should be finished with a soft grain heat	
	resistant, water proof and smooth durable laminate	
	that is friendly to the skin and easy to clean	
	The base to have adjustable plastic tabs for levelling	
	unevenness of the floor.	&
	Color – beech wood	
iii.	Locker for 12 persons	
	3 -column 4-tier locker in in metallic finish with fixed tabs for	
	easy standing.	
	Overall size1200 x 415 x 1850 mm (w x d x h)	
	To have though door hasp (for padlocks)	
	The design should allow for air circulation	
	Each locker to be locked independently and to have	
	a name plate	
iv.	Metallic cabinet	
	1 column, 4-layer metal cabinet 1,324 x 463x 620mm (w x d x	
	h) features;	
	> Key lock to keep file drawer closed and secure.	
	Perfect for conventional or hanging files.	
1	➤ Good quality drawer runners that fit A4 or foolscap	
	files with smart handles.	
	> 100% drawer extension.	
v.	4 bay bulk filer	
	Supply and fix 4 bay manual mobile cabinet, single bay depth	
	complete with anti - tilt, central locking, safety lock, sound	
	buffer pad, powder epoxy coating and backed up to 200 degree,	
	centigrade for fire proofing, chrome plated tracks and dual-	
	purpose shelves (to accommodate both suspended lateral files	
	and box files) adjustment every 25mm height and easy	
	retrieval & reference. It should come with an inbuilt floor	
	filling and cover finish.	

Signature of duly authorised person for and on behalf of the Manufacturer.

Name and Capacity of duly authorised person signing on behalf of the Manufacturer

Kindly sign and stamp as indicated below:

	➤ Standard height – 2,082 mm	
	➤ Standard width- 914 mm	
	➤ Standard depth – 386 mm for single bay	
	➤ Standard depth – 772mm for double bay	
	➤ Standard shelf - 910 x345 x25 mm (w x d x h)	
	➤ Aisle space – 762 mm (minimum)	
	➤ Loading capacity (per shelf) – 50 kg	
	➤ Loading capacity (per bay) – 250kg	
	➤ Weight (per bay) unloaded - 50 kg	
	➤ High density.	
	Accessories – heavy duty shelf for spring & box files.	
vi.	10 bay bulk filer	
	Supply and fix 10 bay manual mobile cabinet, single bay depth	
	complete with anti - tilt, central locking, safety lock, sound	
	buffer pad, powder epoxy coating and backed up to 200 degree	
	centigrade for fire proofing, chrome plated tracks and dual-	
	purpose shelves (to accommodate both suspended lateral files	
	and box files) adjustment every 25mm height and easy	
	retrieval & reference. It should come with an inbuilt floor	
	filling and cover finish.	
	➤ Standard height – 2,082 mm	
	➤ Standard width- 914 mm	
	➤ Standard depth – 386 mm for single bay	
	➤ Standard depth – 772mm for double bay	
	➤ Standard shelf - 910 x345 x25 mm (w x d x h)	
	➤ Aisle space – 762 mm (minimum)	
	➤ Loading capacity (per shelf) – 50 kg	
	➤ Loading capacity (per bay) – 250kg	
	➤ Weight (per bay) unloaded - 50 kg	
	➤ High density.	
	➤ Accessories – heavy duty shelf for spring & box files.	

Kindly sign and stamp as indicated below:
Signature of duly authorised person for and on behalf of the Manufacturer.
Name and Capacity of duly authorised person signing on behalf of the Manufacture

vii.	24 bay bulk filer	
	Supply and fix 24 bay mechanical mobile storage system, 3	
	bay depth complete with anti - tilt, central locking, safety lock,	
	sound buffer pad, round handle, powder epoxy coating and	
	backed up to 200 degree centigrade for fire proofing, chrome	
	plated tracks and dual-purpose shelves (to accommodate both	
	suspended lateral files and box files) adjustment every 25mm	
	height and easy retrieval & reference. It should come with an	
	inbuilt floor filling and cover finish.	
	➤ Standard height – 2,260mm	
	➤ Standard width- 900mm	
	➤ Standard depth – 400mm for single bay	
	➤ Standard depth – 770mm for double bay	
	Standard shelf - 870x370x29 mm (w x d x h)	
	➤ Aisle space – 762 mm (minimum)	
	➤ Loading capacity (per shelf) – 70 kg	
	➤ Loading capacity (per bay) – 350kg	
	Weight (per bay) unloaded - 70 kg	
	➤ High density	
	accessories – heavy duty shelf, spring & box files	
	supply with 1000pc spring file pockets that fit	
D	OTHER	
D	<u>OTHERS</u>	
i.	Binding machine	
	Manual heavy duty binding machine for continuous usage,	
	with;	
	A base suction cap which holds the machine firmly in	
	place during binding	
	Full width handle to allow easier, better balanced punching.	
1	 A punching capacity of (80gsm) - 25 sheets 	
	A binding capacity of (80gsm) - 23 sheets A binding capacity of 500 sheets (80gsm).	
	(Mandatory -Attach brochures and specifications)	
	(stochares and specifications)	

Kindly sign and stamp as indicated below:

Signature of duly authorised person for and on behalf of the Manufacturer.

Name and Capacity of duly authorised person signing on behalf of the Manufacturer

	111 1/211111 0 1/002/1	100
ii.	Medium duty paper shredder	
	Medium duty cross cut paper shredder with the following	
	feature:	
	Cross cut 3.8mm	
	Sheet capacity 26/28 sheets 80gsm.	
	Waste bay volume 100 liters and above	
	➤ Throat 260mm	
	Security level 4	
	Auto reverse motor and drive designed to continuous	
	operation	
	Could shred cds, credit cards etc	
	Mandatory: Attach brochures and specifications.	*
iii.	Smart screen	
	Supply and fix a 70-inch (117.8cm) smart screen television	
	with the following features	
l.	➤ Screen Size 70-inch (1549 x 871) mm (1 x w)	
	Screen Resolution 1920 x 1080	
	Supported Formats	
	Audio-mp3, wav, mp4, wma	
	 Video mp4, avi, mkv, asf, wmv, 3gp, mov, webm Picture jpg, mpo, arw 	
	Smart TV Features	*
	> One-touch Mirroring	
	Screen Mirroring	
	➤ Wi-Fi Connectivity	
	➢ Wi-Fi Direct	
	➤ Internet Video	
	Other features	
	➤ USB Play Yes (USB viewer supports FAT16,	
	FAT32, exFAT and NTFS file systems.)	
	Dynamic Backlight ControlLight Sensor	
	> Power Saving Modes	
	> Power Requirements DC 19.5V	
	> Power Consumption 88 W	
	Standby Power Consumption 0.5 W	
	Supplied Accessories	
	11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	

Kindly sign and stamp as indicated below:

Signature of duly authorised person for and on behalf of the Manufacturer.

Name and Capacity of duly authorised person signing on behalf of the Manufacturer

	4	Remote Control	
	>	HDMI Cable 30m	
	>	Suspended Mounting Brackets	v
	>	VGA cable 30M	
	>	(Mandatory: attach brochures and	
		specifications)	
iv.	. Queue Barrier		
	Supply fully assembled 4-way connectivity queue barrier with		
	double		
	>	Tape to be 7.5" long by 2" wide, dye printed webbing	
		in Kenya Power blue color and logo.	
	>	To have webbing brake system and a locking tape end.	
	>	Base to be metallic – silver/chrome in color and heavy	
		weight base for stability purposes	

Kindly sign and stamp as indicated below:
Signature of duly authorised person for and on behalf of the Manufacturer.
Name and Capacity of duly authorised person signing on behalf of the Manufacturer