

The Kenya Power & Lighting Co. Ltd.

Central Office – P.O. Box 30099, Nairobi, Kenya

Telephone – 254-02-3201000

Fax No. 254-02-3201889

Stima Plaza, Kolobot Road

Our Ref: KP1/9A.2/OT/34/ADMIN/18-19

18th February, 2019

ADDENDUM NO. 1 TO THE TENDER NO. KP1/9A.2/OT/34/ADMIN/18-19 FOR CONSTRUCTION OF KITALE COMMERCIAL OFFICE.

The following amendments are made to the specified provisions of the Tender document.

1. RELATIONSHIP WITH THE PRINCIPAL TENDER DOCUMENT

Save where expressly amended by the terms of this Addendum, the Principal Tender Document shall continue to be in full force and effect.

The provisions of this Addendum shall be deemed to have been incorporated in and shall be read as part of the Principal Tender Document.

2. SECTION VII - BILL OF QUANTITIES (ELECTRICAL INSTALLATIONS)

The bill of quantities for electrical installation was omitted in the tender and are attached herewith.


All the other terms and conditions remain as per the tender document.

Yours faithfully,


For: KENYA POWER & LIGHTING COMPANY LIMITED.

AG. SUPPLY CHAIN MANAGER (PROCUREMENT)

LIGHTING POINTS ghting points wired in 3x 1.5 mm ² SC CU cables awn in 20mm diameter concealed HG P.V.C induits for one way switching couplers, sandles ips junction boxes but excluding the fittings. ghting points wired in 3x 1.5 mm ² SC CU cables awn in 20mm diameter concealed HG P.V.C induits for two way switching couplers, sandles ips junction boxes but excluding the fittings. Induits for two way switching couplers, sandles ips junction boxes but excluding the fittings. Induits for two way switching couplers, sandles ips junction boxes but excluding the fittings.	200	LM LM No.		
ghting points wired in 3x 1.5 mm ² SC CU cables awn in 20mm diameter concealed HG P.V.C induits for one way switching couplers, sandles ips junction boxes but excluding the fittings. In the same of the same o	400	LM		
awn in 20mm diameter concealed HG P.V.C induits for two way switching couplers, sandles ps junction boxes but excluding the fittings. loted Flush mounted 10Amps wide rocker, witch plate as MK or approved equivalent as for the gang one way	9		Section 200	
ritch plate as MK or approved equivalent as for ne gang one way		No.	State Control of the Control	3
Au Table Can		No.	Jane Branch Commence By	
wo gang two way	4	13.4		Carried Boundary
,	4	No.	, .	
wo gang one way	2	No.		2
ree gang One way	2	No.	, 8	k %
LIGHTING FITTINGS ghting fittings complete with electronic ballasts d tubes/lamps as follows:-				D 1
pe A- 1200x36W high frequency surface mounted n section fluorescent light fitting with 28w LED			í	2
es (frostred), white finished steel body and ABS stic end caps as Thorn Modulight or approved livalent	9	No.	E.	19.
	y y		- n	_
pe B-600x600mm 36W slim LED panels frosted. In frequency ceiling luminaire with polycarbonate lay and trim in white polycarbonate diffuser.	72	No.	w 3	-
pe D) - Self contained single sided exit sign with fluorescent lamp for maintained emergency ating for 3 hour duration as Thorn EFX3 c/w CAT XF 7 Euro Legends or approved equivalent	2	No.		
di II	tubes/lamps as follows:- De A- 1200x36W high frequency surface mounted in section fluorescent light fitting with 28w LED as (frostred), white finished steel body and ABS attic end caps as Thorn Modulight or approved invalent De B-600x600mm 36W slim LED panels frosted. In frequency ceiling luminaire with polycarbonate by and trim in white polycarbonate diffuser. De D) - Self contained single sided exit sign with fluorescent lamp for maintained emergency ting for 3 hour duration as Thorn EFX3 c/w CAT CF 7 Euro Legends or approved equivalent	tubes/lamps as follows:- De A- 1200x36W high frequency surface mounted in section fluorescent light fitting with 28w LED es (frostred), white finished steel body and ABS estic end caps as Thorn Modulight or approved invalent De B-600x600mm 36W slim LED panels frosted. In frequency ceiling luminaire with polycarbonate ey and trim in white polycarbonate diffuser are eD) - Self contained single sided exit sign with fluorescent lamp for maintained emergency ting for 3 hour duration as Thorn EFX3 c/w CAT are EF7 Euro Legends or approved equivalent	tubes/lamps as follows:- De A- 1200x36W high frequency surface mounted in section fluorescent light fitting with 28w LED es (frostred), white finished steel body and ABS 9 No. Strice end caps as Thorn Modulight or approved ivalent De B-600x600mm 36W slim LED panels frosted. The frequency ceiling luminaire with polycarbonate and trim in white polycarbonate diffuser and the fluorescent lamp for maintained emergency ting for 3 hour duration as Thorn EFX3 c/w CAT 2 No. The Teuro Legends or approved equivalent	tubes/lamps as follows:- De A- 1200x36W high frequency surface mounted in section fluorescent light fitting with 28w LED es (frostred), white finished steel body and ABS estic end caps as Thorn Modulight or approved invalent De B-600x600mm 36W slim LED panels frosted. In frequency ceiling luminaire with polycarbonate ey and trim in white polycarbonate diffuser . De D) - Self contained single sided exit sign with fluorescent lamp for maintained emergency ting for 3 hour duration as Thorn EFX3 c/w CAT 2 No.



Item	Description	Qty	Unit	Rate (Kshs)	Amount (Kshs)
A	POWER POINTS 3x4 mm ² SC CU cables for twin flush wall mounted socket outlets drawn in 25mm Ø HG PVC conduit from distribution board concealed in walls.	600	LM		
В	13A flush mounted twin piloted white enamel moulded type socket outlet faceplate as MK cat2647 WHI or approved equivalent mounted flush on the wall .	50	No.		
С	45A DP cooker unit + 15A SP switched socket outlet neon indicators and marked cooker.	1	No.		
D	Cooker Connector unit as MK or equivalent	1	No.		-
E,	3x6.0 mm ² SC CU cables drawned in 25mmØ HG PVC conduit from distribution board for cooker point above	60	LM	u .	
F	Piloted 20A DP isolator unit as MK cat 2202CH for undersink instantaneous water heaters	1	No		
G	Power points wired in 3x4 mm ² SC CU cables in concealed 20mm dia HG PVC conduit from distribution board to DP points for items above	- 1	No.		,
Н	AREA/PARKING LIGHTING. 5UV LED 11000 light lamp overall size 200x145.5mm with powder coated steel plate casement with holder complete with integral control gear, wiring in 1.5mm2 twin with earth sheathed cable from the distribution board for a hight of upto 3metres on the wall.	8 8	No.		Audi
I	60A/30mA ELCB as MEM or approved equivalent	1	No.		
J	Photo electric cell (Timer) as THORN cat No. QPK or approved equivalent	1	No.		
K	30 Amps. Triple pole contactor as TELEMECANIQUE or approved equivalent.	1	No.		
7	SUB TOTAL C/F TO PRICE SUMMARY PAGE		2		



						THE RESERVE OF THE PARTY OF THE
L	Item	Description	Qty	Unit	Kate (Kshs)	Amount (Kehe)
	A	5 Metres, top entry, Galvanised steel post for				
		mounting the photocell above.	1	No.		
	В					
		1.5mm ² twin with earth sheathed copper cable drawn in 20 mm dia.PVC conduit from the		,		
		distribution boardPVC/SWA/PVC copper cables				
		complete with appropriate cable glands and lugs	200			
		concealed in walls for security lights.	200	LM		
	C	The following for items 10.1.15 & 10.1.16 above:-				,
		i.) Trenching to a depth of a minimum of 700mm	5	LM		
		ii) Tiling with 'HATARI 'tiles	5	73.6		
		ii) Tiling with 'HATARI 'tiles	3	LM		i
		ii) Back filling of the trenches	5	LM		1
7		the same the considerance of the same that t				
	D	50mm diameter HG PVC ducts with 100 mm thick concrete sorround	5	LM		
		concrete sorround	5	Livi		-1,
	_	POWER DISTRIBUTIONS) :
	E	12way TPN, flush mounted distribution board complete with 125A integral isolator as MEM or				1.1
		approved equivalent complete with all accessories but				
		excluding MCBs.	1	No.		
	F	12way c/w 125A TPN integral isolator	1	No.		
	1	12way 6/w 125A 1114 integral isolator	1	140.		
		Miniature Circuit Breakers (MCB's/RCBOS) for				
ь	G	item 10A SP MCP	4	No.		
2	W			31. 410.		-
	H	20A SP MCB	3	No.		_
	I	30A SP MCB	2	No.		
		Sort of Med	2	140.		1
	J	45A SP MCB	1	No.		191
	K	60A TPN MCB	1	N ₂		
	K	OVA ITIN IVICD	1	No.		
	L	TP blanking plate	9	No.		
_						
		SUB TOTAL C/F TO PRICE SUMMARY PAGE				



Item	Description	Qty	Unit	Rate (Kshs)	Amount (Kshs)
	Earthing, for all electrical installation above of the following and any other necessary accessories to KEBS and KPLC approved standards.:-				
A	12.5 mm x 1200 mm earth rod as FURSE cat. No. RB 105.	1	No.		b
В	12.5 mm dia. Driving stud as FURSE cat.No. ST100.	1	No.		ā
С	Rod to cable clamp as FURSE cat. No. CR510.	1	No.		
D	Concrete inspection pit as FURSE cat. No.PT005. (or a well made 320mm x 320mmx 210 mm depth pit.)	1	No.		
Е	6mm sq. SC PVC CU cables drawn in 20 mm dia.PVC conduit concealed in walls.	20	LM		and the same and the light
		2			
	,) **.	1			
		,		9	
		90 /			
		-			
11: ±		2	* g*		4 500
	*				

Domasna

SUB TOTAL C/F TO PRICE SUMMARY PAGE

	The u	(*X					
SUMMARY							
ITEM	DESCRIPTION			AMC	UNT		
1	Total from page 1			KSHS	CTS		
2	Total from page 2		-				
3	Total from page 3		side.				
4	Total from page 4		_				
5	Allow for production of 3 copies of as installed drawings						
	TOTAL C/F TO GRAND SUMMARY				i		
Total amount in words :, Kenya							
m - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -							

Tender	er's Name and Stamp		
	PinNo	VAT Certificate	
	Witness	Address	
Signatı Witnes:		Date	



¥